

# 5716 **ALLEVARD**

«Medium» version in the orientable recessed round lights

Spotlight swivels 360° in its recess to direct the beam in the right direction with no installation constraints.

LED plate is tiltable (+/25°) by external adjustment without opening the fitting or compromising its water resistant.


#### **APPLICATIONS:**

- Low facade lighting (5m)
- Highlight architectural features, street furniture, small trees...

#### CARACTERISTICS

- · Anodised aluminium body
- Vandalproof organic glass window
- 316L Stainless steel screws
- · Flush-recessed
- 2 possible recess dimensions
- Withstands occasional traffic from all kinds of vehicles
- RGBW options available





Number of LEDs 6.7

Type of LEDs Power LEDs. Contact us for hot countries.

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/5716-allevard-r97

### APPLICATION




Outdoor lighting

Standard flux: 1561 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

#### MOUNTING TYPE

Ground flush recessed fittings




#### **CARACTERISTICS**

Weight: 2300 g


#### **Options of luminous effects**



RGBW option








Transparent flat window





## **Power supply - Control**

Cable length: 1 m

## Material

(AL) Anodised glazed aluminium

316L Stainless steel

Vandalism-proof, scratchproof, UV-proof, polycarbonate window, M2

#### **Mechanical strength - Waterproofness**

Withstands random all vehicles traffic

IK10 Resists impacts up to 60 60J joules (IK10)

Tight for extended IP68 immersion

Adjustable orientation without dismantling



## **5716 ALLEVARD**

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product: http://www.lec-lyon.com/5716-allevard-r97

